LV cables Tools

PINTEL4BT/1216-1000V

Certifications

EN 60900:2012 - Approved by ENEDIS

Section

LV Live working

Application

Field
Laboratory
Production

Live line stripping pliers for Low-Voltage secondary distribution cable's outer jacket.

TO DO WHAT

The PINTEL4BT/1216-1000V enables to make a circular and longitudinal cut on Live line Low-Voltage underground secondary distribution cable in order to remove cable's outer jacket.



PRODUCT BENEFITS

Swinging cable support for a better guidance
1000V Insulated EN 60900: 2012
All cutting depth ranging from 0,5 mm / 0,020 in to 5 mm / 0,197 in are available on demand.
Maximum cutting depth for the cutting head with 3 positions : 3,5 mm / 0,138 in

TOOL CAPACITY

Diameter	10 - 30 mm 0,394 - 1,181 inch
Circular cutting thickness capacity (mm/inch)	1,2 mm / 0,047 in
Longitudinal cutting thickness capacity (mm/inch)	1,6 mm / 0,063 in

TOOL DIMENSIONS

Length	260 mm
Width	90 mm
Height	80 mm
Weight without box	0,66 Kg

Options

SGM - Large size pouch

Spare part

MTLP4/16 - Spare blade for longitudinal cutting 1,6 mm / 0,063 in
MTCP4/12 - Spare blade for circular cutting 1,2 mm / 0,047 in (x3)

Associated tool

PINTEL4BT/1216R1000V - Live line stripping pliers for Low-Voltage sec distribution cable's outer jacket
PINTEL4BT/1216 - Stripping pliers for Low-Voltage secondary distribution cable's outer jacket

ALROC SAS
Z.I. de la Fonderie - 72160 TUFFE FRANCE
Phone: +33 2 43 71 11 80
Fax number : +33 2 43 71 16 51
www.alroc.fr

LV cables Tools

PINTEL4BT/1216-1000V

Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Circular cutting thickness capacity (mm/inch)	Longitudinal cutting thickness capacity (mm/inch)	Length	Width	Height	
PINTEL4BT/1216-1000V	10 - 30 mm 0,394 - 1,181 in	1,2 mm / 0,047 in	1,6 mm / 0,063 in	260 mm 10,236 in	90 mm 3,543 in	80 mm 3,150 in	box